

PYRO**Charcoal
Multiuse
Stove****Specifications**

Stove Diameter	Vessel Diameter	Fuel required per hr.	* Max. price in Rupees (Taxes as applicable)
1.3 Feet	33-40 cm.	0.7 Kgs. charcoal	10250-00
1.6 Feet	43-50 cm.	1-1.5 Kgs. charcoal	14000-00
2.0 Feet	53-60 cm.	1.5-2 Kgs. charcoal	17000-00

Insulated with **cold face insulation bricks**.

To enable controlled burning of fuel, **cast iron grate** is provided.

Ash box is present for safe collection of ash.

Air regulator holes is present for controlling flame level.

Manufactured from mild steel.

Colour - Red.

Chimney made of ferro cement is provided to have a smokeless, hygenic environment.

**PYRO****Stainless
Steel
Tea Boiler****Specifications**

Milk Capacity	Water Capacity	Fuel required per hr.	* Max. price in Rupees (Taxes as applicable)
10 Ltr.	25 Ltr.	2-2.5 Kgs. firewood	25000-00
		0.8-1 Kgs. charcoal	

Insulated with **ceramic blanket**.

To enable controlled burning of fuel, **cast iron grate** is provided.

Ash box is present for safe collection of ash.

Air regulator door with holes is present for controlling flame level.

Manufactured from stainless steel.

Colour - Silver.

* Last Mile Transportation & Installation Charges Extra

Sustaintech India Pvt. Ltd.

Corporate Office : No.19, 9th Cross, 6th Main,
Malleswaram, Bengaluru - 560003 Ph: 080-23344555

Head Office: 22/74A, Deputy Collector's Colony, 2nd Street,
K.K.Nagar, Madurai - 625010 Ph: 0452-4200562

Email: info@sustaintech.in www.sustaintech.in

PYRO

Thrift • Savings • Profit

**FUEL SAVINGS
UPTO****50%**

**Certified by CPRI
(Central Power
Research Institute)
on fuel Savings.**

**Now with
1 year Warranty**

- **Tea Boilers**
- **Tava Stoves**
- **Multiuse Stoves**
- **Charcoal Multiuse Stoves**
- **Loose Biofuel Stoves**

**Manufactured with
New Technology**

Sustaintech India Pvt. Ltd.

SUSTAINTECH

PYRO

Tava Stove



Specifications

Length	Width	Tava plate Thickness	Time taken for plate to get hot	No. of 30cm dia. dosas that can be baked in 3 mnts	No. of 10cm dia. parotas that can be baked in 6 mnts	Fuel required for 1 hr. (firewood in Kgs.)	* Max. price (Taxes as applicable) in Rupees
3 Feet	2 Feet	0.63 inch	15-20 mnts	3	35	4-5	24,500-00
3 Feet	2 Feet	0.75 inch	15-20 mnts	3	35	5-6	28,000-00
3 Feet	2 Feet	1.00 inch	15-20 mnts	3	35	5-6	30,000-00
4 Feet	2.5 Feet	0.75 inch	15-20 mnts	4	60	6-8	43,000-00
4 Feet	2.5 Feet	1.00 inch	15-20 mnts	4	60	6-8	47,000-00
4 Feet	3 Feet	1.00 inch	15-20 mnts	5	75	6-8	52,000-00

Insulated with **cold face insulation bricks**.
 To enable controlled burning of fuel, **cast iron grate** is provided.
Ash box is present for safe collection of ash.
Air regulator door is present for controlling flame level.
 Height – 3 feet from ground level.
 Manufactured from mild steel.
 Colour – Orange.

Smokeless stove. As stove body is insulated heat does not escape through sides and cooking can be done comfortably. There is no change in manner of cooking.



PYRO

Multiuse Stove



Specifications

Stove Diameter	Rice cooking time (40-45 mnts.)	Sambar/Dal cooking time (1 hr.)	Oil heating time (20 mnts.)	Vessel Diameter	Fuel required per hr.		* Max. price in Rupees (Taxes as applicable)	
					Firewood	Briquettes	Firewood	Briquettes
1.3 Feet	70 persons 6 Kgs.	16 Ltr.	15 Ltr.	33-40 cm.	2.5 Kgs.	1-1.5 Kgs.	9000-00	11000-00
1.6 Feet	71-120 persons 11 Kgs.	17-30 Ltr.	15-19 Ltr.	43-50 cm	4.0 Kgs.	2.0 Kgs.	12000-00	15000-00
2.0 Feet	121-180 persons 16 Kgs.	31-45 Ltr.	19-25 Ltr.	53-60 cm	4-5 Kgs.	2.5 Kgs.	15000-00	18000-00

Insulated with **cold face insulation bricks**.
 To enable controlled burning of fuel, **cast iron grate** is provided.
Ash box is present for safe collection of ash.
Air regulator holes is present for controlling flame level.
 Manufactured from mild steel.
 Colour – Blue.

Air Regulator holes are present to control level of flame. Less Maintenance. Safe to use.
 As the stove gets heated fast and retains heat for a long time, fuel savings will be there upto 50% when compared to conventional stoves.



PYRO

Loose Bio-fuel Stove



Specifications

Stove Diameter	Rice cooking time (30-35 mnts.)	Sambar/Dal cooking time (45 mnts.)	Oil heating time (15 mnts.)	Vessel Diameter	Fuel required per hr.	* Max. price in Rupees (Taxes as applicable)	
						Firewood	Briquettes
2.1 Feet	121-180 persons 16 Kgs.	31-45 Ltr.	19-25 Ltr.	57-64 cm.	4-5 Kgs.		18000-00
2.4 Feet	181-200 persons 11 Kgs.	46-48 Ltr.	26-28 Ltr.	67-74 cm.	6-7 Kgs.		20000-00

Insulated with **cold face insulation bricks**.
 To enable controlled burning of fuel, **cast iron grate** is provided.
Ash box is present for safe collection of ash.
Air regulator holes is present for controlling flame level.
 Fuels that can be used – Cashew shells, Wood Shavings, Tamarind Shells, Groundnut shells etc.
 Manufactured from mild steel.
 Colour – Orange.



To enable controlled burning of fuel

← **Briquette cast iron Grate**

Charcoal cast iron Grate →

